



LUXAR® Classic New Generation- Interference optical thin film coated glass

Technical advice

LUXAR® Classic New Generation is an anti reflective coated glass that reduces glare and reflection almost 100% which allows the user to show pictures, merchandize or even a view in a way that was never achievable before. The coating is made with metalloxides that are sputtered onto float glass or other other substrates. LUXAR® Classic New Generation can be processed just as regular float glass, it can be tempered, laminated (PVB or resin), insulated, bent, drilled, etc. Even though it is a hard coating care should be taken while handling the glass in the processing of the product (refer to handling procedures).

The Luxar coating is applied so that glare is virtually invisible when viewed at 90 degrees. Under special light conditions and angles of view, one can see small differences in the reflection and small iridescent light effects. These effects are inherent with the manufacture of Luxar and are not subject for a claim.

Instructions for planing

LUXAR® Classic New Generation should be protected from rain runoff and the weathering of steel and other building materials. Either the building owner should regularly maintain the glass by cleaning stains or the glass should not be used in that environment.

Danger – people have to be protected against “walking through LUXAR® glass”. Luxar is “invisible” and if the glass is used in an application where people could accidentally wald into the glass then the glass must be marked a way that people are protected from injuring themselves.

Installation instruction

Before and after installing the glass you have to preserve the coating against mechanical damage (scratch). When transporting, putting it in stock and every kind of handling you have to take care about **clean** supports, layers, tools, suction etc. Keep the LUXAR® Classic New Generation in a dry and UV protected environment (closed area). Do not expose the glasses with the protective film to sunlight.

If you insulate LUXAR® remove excess sealant material immediately. Avoid using too much solvent to remove the excess sealant. During the installation of LUXAR® avoid job site materials from getting on the glass or remove any spilled material immediately, this includes concrete, lime, stucco, etc. When removing materials that are abrasive such as concrete use plenty of water and try not to rub the material as it will scratch the glass. Always use cleaning cloths that are clean and not abrasive.

Cleaning

LUXAR® Classic New Generation should be cleaned on a regular basis. Never let dirt or stains remain on the glass. Normally it's enough when you just use water and sponge or cloth to clean the glass. If it's needed you can use detergent e.g. Windex, Glass Plus, etc.

It's better not to put any kind of stickers on the LUXAR® glass, because you can damage the coating when removing the sticker.

Products NOT to use with LUXAR® Classic New Generation

Do not use strong alkalis, acids, detergents with fluoride, solvents as they will destroy the coating. Do not use detergents with mechanical devices (sand etc.) nor other mechanical millinery. Do not use blades; steel blades may hurt the surface and cause scratches.

If you do not follow the cleaning instructions the manufacturer will not be responsible for warranty.

Warranty

For LUXAR® Classic New Generation anti-reflective coated glass, Glas Trösch AG, HY-TECH-GLASS will guarantee that under normal use and conditions the transmission and coating will not change.

Glas Trösch AG, HY-TECH-GLASS will replace LUXAR® within 5 years from date of purchase if defects occur in the coating. The sole responsibility of Glas Trösch AG, HY-TECH-GLASS is to replace the defective material only. It does not cover any costs associated with removal or replacement of the product. The warranty does not cover damage caused by misuse, neglect or accident. The warranty is non-transferable.

If LUXAR® Classic New Generation is insulated the warranty will be given from the separate manufacturer.

2008/03/17

